



1615

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 45 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- Maximum airline check-in size*
- *Check with your airline for exact measurement requirements
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1615
Standard

1615NF
No Foam

1615WD
With Padded Dividers

1615TP
With TrekPak Divider System

1615WF
With Foam

DIMENSIONS

Interior (LxWxD)	29.59 x 15.50" x 9.38 (75.2 x 39.4 x 23.8 cm)
Exterior (LxWxD)	32.58 x 18.40" x 11.02 (82.8 x 46.7 x 28 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	7.38" (18.7 cm)
Total Depth	9.38" (23.8 cm)
Int Volume	2.49 ft ³ (0.071 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

■ Orange

■ Silver

■ Yellow

WEIGHT

Weight With Foam	17.60 lbs (8 kg)
Weight Empty	14.06 lbs (6.4 kg)
Buoyancy	169.20 lbs (76.7 kg)


TEMPERATURE

Minimum Temperature	-60°F (-51.1 °C)
Maximum Temperature	160°F (71.1 °C)


OTHER

Wheels	2
---------------	---


ACCESSORIES



1615AirFS
7 pc. Replacement Foam Set



1615TP-KIT
TrekPak Case Divider Kit



1615TPKIT
TrekPak Case Divider Kit



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-03-23